



Apollo XL



100
Snow



170
Delaware



515
Pyrenees



525
Alpine Gum



540
Natural Fumed Oak




545
Blackbutt



550
Aged Fumed Oak



555
Spotted Gum



570
Wellington



720
Reclaimed Oak



730
Boston



790
Midnight



While all care is taken, product images may vary in colour due to possible printing process variations. Images are to be used as a guide only to give an idea of the colour and nuances of the pattern, but are not fully representative of the variations among the planks (which reflects the natural product which inspired the design). For a representative view of the surface structure and variations within the design, take a look at the big samples on display and ask your retailer for more advice.
*Subject to proper installation, maintenance and local building code/regulatory approval.

Apollo XL

Apollo XL is a stunning hybrid floor that is extremely hard wearing, stable and waterproof[†], making it perfect for use in all areas of your home. With micro bevel edges and an embossed matte finish, Apollo XL authentically replicates a natural timber wood grain look. A scratch and stain resistance surface coating means Apollo XL can easily withstand the everyday wear and tear of busy family homes.

Technical Data

Type	Hybrid	Finish	Matte
Plank Thickness	6.5mm	Surface	Embossed
Wear Layer	0.5mm	Top Layer	Decorative Film & Wear Layer
Dimensions	1500mm (L) x 180mm (W)	Substrate Layer	Trigon [®] Core Technology (Limestone Composite)
Planks per Box	6	Backing Layer	1.5mm EVA
M² per Box	1.62m ²	Profile	Micro Bevel
M² per Pallet	113.40m ²	Protective Coating	PUR & Scratch Resistance
Colours	12		
Installation Method	UNIPUSH [®]		

Performance

Dimensional Stability	Length: 0.05% Width: -0.00% Curling: 0.00%	ISO 23999
Thermal Resistance	0.056m ² .K/W	EN 12667
Thermal Conductivity	0.115 W/(m.K)	EN 12667
Abrasion Rating	Group T	EN 660-2
Swelling After Submersion in Water	0.3%	ISO 24336
Impact Sound Reduction	Test Application	Ln'T,w Result
	150mm Slab + 28mm Furrings + 10mm Plasterboard	50
	200m Slab	54
	200mm Slab + 28mm Furrings + 10mm Plasterboard	49
	200mm Slab + R2.5 Insulation + 100mm Cavity + 10mm Plasterboard	46
	250mm Slab + 28mm Furrings + 10mm Plasterboard	48
Light Fastness	Grade 6	ISO 105-B02
Fire Classification	CRF 10.9kW/m ² Smoke Value 81% minutes	EN ISO 9239
Slip Resistance	P3	AS 4586
Residential Warranty*	25 Year Hybrid Limited Residential Warranty	
Commercial Warranty[†]	15 Year Commercial Warranty available upon request	

Sustainability

VOC Rating	Passes CETEC VOC Test
Global GreenTag	GreenRate Level A certified



Manufactured under a quality and environmental system certified as complying with ISO9001 and 14001. Test results and certificates are available on request. Specifications and colourations are subject to manufacturing tolerances. As part of Godfrey Hirst's continuous improvement process, Godfrey Hirst reserves the right to change the specifications or delete colours of this product without notice. All Godfrey Hirst Hybrid Floors must be installed in accordance with relevant Australian Standards and in conjunction with the Godfrey Hirst Hybrid Floors Installation Instructions. *This product comes with a residential warranty for new product installed indoors in a residential home, if properly installed and maintained. This warranty is in addition to consumers' rights under the statutory consumer guarantee provisions in the Australian Consumer Law, which may exceed the rights under this warranty. The amount recoverable under the warranty decreases after five years. For full information in respect to the scope and limitations of this warranty, please refer to the full terms and conditions available from your retailer, by calling 1300 444 778, or by download from www.godfreyhirst.com. [†]Terms and conditions apply to all commercial warranties – contact your Godfrey Hirst account manager.