



Metropol 1500



100
Alabaster



180
Burnt Umber



300
Sable Oak



500
Cornsilk



520
Brass Oak



545
Apple-Box Gum



555
Marble Spotted Gum



560
Burl Oak



580
Fallow Oak



700
Platinum Grey



720
Pepper Oak



790
Silhouette Oak



While all care is taken, product images may vary in colour due to possible printing process variations. Images are to be used as a guide only to give an idea of the colour and nuances of the pattern, but are not fully representative of the variations among the planks (which reflects the natural product which inspired the design). For a representative view of the surface structure and variations within the design, take a look at the big samples on display and ask your retailer for more advice.
*Subject to proper installation, maintenance and local building code/regulatory approval.

Metropol 1500

Delivering super durable and impact resistant flooring with exquisite design, Metropol 1500 is a technologically advanced hybrid range that ticks all the right boxes. Available in a wide range of natural timber hues, your next project is a guaranteed winner with strong, stable and beautiful flooring that's easy to install.

Technical Data

Type	Hybrid	Finish	Matte
Plank Thickness	6.5mm	Surface	Embossed
Wear Layer	0.5mm	Top Layer	Decorative Film & Wear Layer
Dimensions	1500mm (L) x 228mm (W)	Substrate Layer	Trigon® Core Technology (Limestone Composite)
Planks per Box	6	Backing Layer	1.5mm IXPE
M² per Box	2.05m ²	Profile	Micro Bevel
M² per Pallet	123.12m ²	Protective Coating	PUR
Colours	12		
Installation Method	Uniclic®		

Performance

Dimensional Stability	Length: 0.0 Width: 0.0 Curling 0.0	ISO23999																								
Thermal Resistance	0.039m ² K/w	ISO 8301																								
Thermal Conductivity	0.128 W/(m.K)	ISO 8301																								
Abrasion Rating	Group T	EN 660-2																								
Swelling After Submersion in Water	0.1%	ISO 24336																								
Impact Sound Reduction	<table border="1"> <thead> <tr> <th>Test Application</th> <th>Ln'T,w Result</th> </tr> </thead> <tbody> <tr> <td>150mm Slab + 28mm Furrings + 10mm Plasterboard</td> <td>51</td> </tr> <tr> <td>200m Slab</td> <td>55</td> </tr> <tr> <td>200mm Slab + 28mm Furrings + 10mm Plasterboard</td> <td>50</td> </tr> <tr> <td>200mm Slab + R2.5 Insulation + 100mm Cavity + 10mm Plasterboard</td> <td>47</td> </tr> <tr> <td>250mm Slab + 28mm Furrings + 10mm Plasterboard</td> <td>49</td> </tr> </tbody> </table>	Test Application	Ln'T,w Result	150mm Slab + 28mm Furrings + 10mm Plasterboard	51	200m Slab	55	200mm Slab + 28mm Furrings + 10mm Plasterboard	50	200mm Slab + R2.5 Insulation + 100mm Cavity + 10mm Plasterboard	47	250mm Slab + 28mm Furrings + 10mm Plasterboard	49	ISO140-7 / ISO717.2												
Test Application	Ln'T,w Result																									
150mm Slab + 28mm Furrings + 10mm Plasterboard	51																									
200m Slab	55																									
200mm Slab + 28mm Furrings + 10mm Plasterboard	50																									
200mm Slab + R2.5 Insulation + 100mm Cavity + 10mm Plasterboard	47																									
250mm Slab + 28mm Furrings + 10mm Plasterboard	49																									
Light Fastness	≥6	EN ISO 105-B02																								
Light Reflectance Values	<table border="1"> <tbody> <tr> <td>100 Alabaster</td> <td>46.14 %</td> <td>180 Burnt Umber</td> <td>8.60%</td> <td>300 Sable Oak</td> <td>18.44%</td> </tr> <tr> <td>500 Cornsilk</td> <td>30.04%</td> <td>520 Brass Oak</td> <td>22.30%</td> <td>545 Apple-Box Gum</td> <td>20.90%</td> </tr> <tr> <td>555 Marble Spotted Gum</td> <td>12.32%</td> <td>560 Burl Oak</td> <td>11.41%</td> <td>580 Fallow Oak</td> <td>15.47%</td> </tr> <tr> <td>700 Platinum Grey</td> <td>33.98%</td> <td>720 Pepper Oak</td> <td>19.10%</td> <td>790 Silhouette Oak</td> <td>13.31%</td> </tr> </tbody> </table>	100 Alabaster	46.14 %	180 Burnt Umber	8.60%	300 Sable Oak	18.44%	500 Cornsilk	30.04%	520 Brass Oak	22.30%	545 Apple-Box Gum	20.90%	555 Marble Spotted Gum	12.32%	560 Burl Oak	11.41%	580 Fallow Oak	15.47%	700 Platinum Grey	33.98%	720 Pepper Oak	19.10%	790 Silhouette Oak	13.31%	
100 Alabaster	46.14 %	180 Burnt Umber	8.60%	300 Sable Oak	18.44%																					
500 Cornsilk	30.04%	520 Brass Oak	22.30%	545 Apple-Box Gum	20.90%																					
555 Marble Spotted Gum	12.32%	560 Burl Oak	11.41%	580 Fallow Oak	15.47%																					
700 Platinum Grey	33.98%	720 Pepper Oak	19.10%	790 Silhouette Oak	13.31%																					
Fire Classification	CRF 11.1kW/m ² Smoke Value 210% minutes	ISO 9239																								
Slip Resistance	P3	AS 4586																								
Residential Warranty*	25 Year Hybrid Limited Residential Warranty																									
Commercial Warranty†	10 Year Commercial Warranty available upon request																									

Sustainability

Indoor Air Quality Green Building Council compliant for VOC emission rate limits



Manufactured under a quality and environmental system certified as complying with ISO9001 and 14001. Test results and certificates are available on request. Specifications and colourations are subject to manufacturing tolerances. As part of Godfrey Hirst's continuous improvement process, Godfrey Hirst reserves the right to change the specifications of or delete colours of this product without notice. All Godfrey Hirst Hybrid Floors must be installed in accordance with relevant Australian Standards and in conjunction with the Godfrey Hirst Hybrid Floors Installation Instructions. *This product comes with a residential warranty for new product installed indoors in a residential home, if properly installed and maintained. This warranty is in addition to consumers' rights under the statutory consumer guarantee provisions in the Australian Consumer Law, which may exceed the rights under this warranty. The amount recoverable under the warranty decreases after five years. For full information in respect to the scope and limitations of this warranty, please refer to the full terms and conditions available from your retailer, by calling 1300 444 778, or by download from www.godfreyhirst.com. †Terms and conditions apply to all commercial warranties – contact your Godfrey Hirst account manager.