



# Belle XL



110  
**Salt Lake**  
Oak



180  
**Woodstock**  
Oak



320  
**Husk**  
Oak



350  
**Taylor**  
Oak



500  
**Nordic**  
Oak



520  
**Coastal**  
Oak



540  
**Driftwood**  
Oak



550  
**Desert**  
Oak



580  
**Castlerock**  
Oak



710  
**Sterling**  
Oak



730  
**Misty**  
Oak



790  
**Raven**  
Oak



\*Subject to proper installation and maintenance. While all care is taken, product images may vary in colour due to possible printing process variations. Images are to be used as a guide only to give an idea of the colour and nuances of the pattern, but are not fully representative of the variations among the planks (which reflects the natural product which inspired the design). For a representative view of the surface structure and variations within the design, take a look at the big samples on display and ask your retailer for more advice.

# Belle XL

Accentuate the grand space in a room with the ultimate in elegant style and affordability. Belle XL laminate planks are not only extra wide at 240mm, but each plank is an incredible 2050mm long, allowing you to create stunning interior style with a practical laminate floor.

## Technical Data

Type	Laminate	Country of Origin	Belgium
Plank Thickness	8mm	Finish	Soft Touch Matte
Dimensions	2050mm (L) x 240mm (W)	Surface	Embossed
Planks per Box	7	Substrate Layer	850kg/m <sup>3</sup> High Density Fibreboard
M <sup>2</sup> per Box	3.444m <sup>2</sup>	Backing Layer	Balancing Layer
M <sup>2</sup> per Pallet	113.652m <sup>2</sup>	Profile	Micro Bevel
Colours	12	Installation Method	FitXpress®

## Performance

Classification	23, 32	ISO 10874	
Static Indentation	≤0.05mm	EN433	
Abrasion Rating	AC4	EN 13329	
Swelling After Submersion in Water	≤12%	ISO 24336	
Impact Sound Reduction	<b>Test Application</b>	<b>Ln'T,w Result</b> Underlay: 2.0mm IXPE	
	150mm Slab + 28mm Furrings + 10mm Plasterboard	51	
	200m Slab	55	ISO140-7 /
	200mm Slab + 28mm Furrings + 10mm Plasterboard	50	ISO717.2
	200mm Slab + R2.5 Insulation + 100mm Cavity + 10mm Plasterboard	47	
250mm Slab + 28mm Furrings + 10mm Plasterboard	49		
Light Fastness	Class 8 – Blue Reference	EN ISO 105-BO2	
Fire Classification	CRF 6.1 k/Wm <sup>2</sup>	AS ISO 9239	
	Smoke Value 11%.min		
Slip Resistance	P3	AS 4586	
Residential Warranty*	25 Year Laminate Limited Residential Warranty		
Commercial Warranty†	7 Year Commercial Warranty available upon request		

## Sustainability

VOC Rating	CETEC Compliant for VOC Emission Rate Limits
------------	--



Manufactured under a quality and environmental system certified as complying with ISO9001 and 14001. Test results and certificates are available on request. Specifications and colourations are subject to manufacturing tolerances. As part of Godfrey Hirst's continuous improvement process, Godfrey Hirst reserves the right to change the specifications of or delete colours of this product without notice. All Godfrey Hirst laminate floors must be installed in accordance with relevant Australian Standards and in conjunction with the Godfrey Hirst Laminate Floors Installation Instructions. \*These residential warranties are in addition to consumers' rights under the statutory consumer guarantee provisions in the Australian Consumer Law, which may exceed the rights under these warranties. Conditions apply: Warranties apply to residential indoor use of the floor installed and maintained in accordance with Godfrey Hirst's guidelines. The amount recoverable under the warranties decreases after five years. For full information in respect to the scope and limitations of these warranties, refer to the Godfrey Hirst Laminate Floors Care, Maintenance and Warranties guide (which also includes full information as to the installation, care and characteristics of Godfrey Hirst laminate products) available from your retailer, by calling 1300 444 778, or by download from [www.godfreyhirst.com](http://www.godfreyhirst.com). †Terms and conditions apply to all commercial warranties – contact your Godfrey Hirst account manager.